

Profile for printing on a wire with a diameter of 4.5mm-5.4mm, cross-section 6mm², yellow 100m



Product description

Profile for printing on a wire with a diameter of 4.5mm-5.4mm, cross-section 6mm², yellow 100m, made of self-extinguishing PVC

RP – a profile for printing wire and cable markers.

RP is made of self-extinguishing PVC material, resistant to weather conditions.

Perfect for printing with MARKERS LK330 thermal transfer printers, Canon Mk 2600/5000 printers, and others. Easy to use, designed for all available wire and cable cross-sections/diameters.

Features and applications:

RP is suitable for thermal transfer printing.

Operating temperature: -20 to 140 degrees C.

RP is made of self-extinguishing PVC material, resistant to weather conditions. Flammability class: V0, ROHS compliant.

WŁAŚCIWOŚCI

- made of self-extinguishing PVC
- working temperature - 30 C to +60 C
- stable UV print

TYP	ŚREDNICA min/max	PRZEKRÓJ mm ²	OPAKOWANIE
RP*050	1,6 mm-2,1 mm	0,5	rolka 100 m lub 50 m
RP*075	2 mm-2,5 mm	0,75	rolka 100 m lub 50 m
RP*100	2.2 mm-2.7 mm	1	rolka 100 m lub 50 m
RP*150	2,6 mm-3,3 mm	1,5	rolka 100 m lub 40 m
RP*250	3,2 mm-4 mm	2,5	rolka 100 m lub 40 m
RP*400	3,8 mm-4,6 mm	4	rolka 100 m lub 25 m
RP*600	4,5 mm-5,4 mm	6	rolka 100 m lub 25 m
RP*10U	6 mm - 7,5 mm	10	rolka 100 m lub 25 m

